



1.Purpose:

The watertight and oiltight hatch with oval cover is designed for mounting in a bunkers and tanks on the ships about permissible pressure above atmospheric to 3 Bar from the inside.

2.Characteristics:

The hatch is built according to DIN 83402 Standard.

The frame and the cover are made of steel grade A (RST-37) acc. PN-93/H-92147, for B,C and D type in a welded version.

Screws and nuts made of galvanized steel. Screws are united by pressure welding with the frame of monhole.

The rubber gasket according to DIN 83403 Standard is engine fuel - proof, lubricating oils - proof, petroleum - proof, sea water - proof and brackish - water - proof in temperature range from -25 to +80°C and about permissible pressure to 3 Bar.

Other dimensions, outfit and versions, to be agreed with Manufacturer

3.Finish:

The hatch is painted in painting set no M38

4.Classification and designation:

- types acc. to the drawing
- dimensions acc. to the table

When ordering, please specify the following items in succession:
name, type, dimension, number of drawing, example:

HATCH A - 420 x 620 x 12 acc. to N19/34.106

SEIMI

75, rue Amiral Troude, CS41809, 29218 BREST CEDEX 2.

Tél: +33 (0)2 98 46 11 02 Fax: +33 (0)2 98 43 37 49

info@seimi.com www.seimi.com